

AOSIF Cummins Series

Product introduction



Model AC110-I Generator set

100KVA/80KW



XIAMEN AOSIF ENGINEERING LTD.

General Performance Data

Prime Power	100KVA/80KW
Stand by Power	110KVA/88KW
Frequency/Speed	50Hz/1500rpm
Rated Power Factor($\cos\phi$)	0.8
Standard Voltage	230V/400V
Phases	3



Engine	Brand	Cummins
	Model	4BTAA3.9-G3
Control module	Deepsea 6120	
Rated Current	144A	
Capacity of Breaker	160A	
Starting Voltage	DC24V	

Fuel consumption

Rated output	Fuel consumption rate	
100%Standby	215 g/KW.h	27.6 L/h
100%Prime	212 g/KW.h	24.7 L/h
75%Prime	208 g/KW.h	18.2L/h
50%Prime	211 g/KW.h	12.3 L/h
25%Prime	237 g/KW.h	6.9L/h

Standards followed

ISO9001	ISO14001
ISO8528	ISO12100
ISO13849	EN12601
GB12786	GB/T2820
IEC60034	IEC60204
CE	RETIE



Dimensions and Weights

Type	Open	Silent
Length(mm)	2100	2500
Width(mm)	760	1000
Height(mm)	1400	1600
Weight(kg)	1100	1750
Base fuel tank volume (L)	215	215

Engine specification

Basic parameter		Air induction system	
Manufacturer	dongfeng Cummins	Maximum Intake Air Restriction with Heavy Duty Air Cleaner	
Model	4BTAA3.9-G3	---Dirty Element	3.7 kPa
No. of cylinder	4	---Clean Element	6.2 kPa
Type	4 cycle, Vertical In-line		
Prime Power	96kw /129HP		
Standby Power	106kw /142HP		
Aspiration	Charge Air Cooled	Exhaust system	
Governor	Electronic	Maximum Back Pressure	10 kPa
Bore x Stroke	102x120 mm		
Displacement	3.9 L		
Compression ratio	18.0:1	Cooling system	
Oil Capacity(Total)	10.9 L	Coolant capacity	
Coolant Capacity(Engine only)	7.2 L	---Engine only	7.2 L
Cranking Motor Voltage	DC24V	---Total system	N/A
Fuel System		Maximum Coolant Friction Head External to Engine	35 kPa
Type Injection system	WF PW/Electronic Governor	Maximum Static Head of Coolant Above Engine Crank Centerline	18.3 m
Fuel consumption	24.7 L/h	Standard Thermostat (Modulating) Range	83-95 °C
Lubrication system		Minimum Pressure Cap	48 kPa
Normal operating oil pressure range		Electric system	
---Idle Speed(Minimum)	207 kPa	Cranking Motor (Heavy Duty, Positive Engagement)	DC 24V
---Governed Speed(Maximum)	345 kPa	Minimum Recommended Battery Capacity	
Maximum Oil Temperature	121 °C	---Cold Soak @ 0 to 32-F (-18 to 0-C)	312 CCA
Minimum Required Lube System Capacity - Sump plus Filters	10.9 L	Battery Charging System, Negative Ground	40 A
		Maximum Allowable Resistance of Cranking Circuit	0.002 ohm


Alternator specification

Phases	3	Coating	Vacuum impregnation
Poles	4	Insulation class	H
Power factor(cosφ)	0.8	Protection	IP23
Winding connection	Star	Excitation system	Self-excited
Winding pitch	2/3	Bearing	Single Bearing
Voltage regulator type	AVR	Coupling	Flexible disc

Control system Introduction

Deepsea 6120 Auto start & auto mains failure control panel

Deepsea 6120 is an auto mains failure controller for single generator, it can monitor and protect the generator working all the time. it has a LCD display which clearly shows the status of the engine. this controller include seven inputs and six outputs. This controller can also be programmed using the front panel or by using DSE configuration Suite PC software



Key Features:

- Auto start/stop, load transfer and alarming of generator
- Remote start on or off load
- With hierarchical loading function
- Multiple start/stop cycles can be preset
- 3 phase generator and mains voltage monitoring.
- Generator/load power detection(kW, kVA, kVAr PF)
- Overload protection (kW)
- Load current monitoring and protection
- Engine speed protection
- Engine pre-heat
- Engine start idle & stop idle
- Battery voltage monitoring
- Start under the low battery
- 4 active outputs
- 4 digital inputs and 3 analogue inputs.
- 6 Custom digital input
- 6 outputs(4 configurable on magnetic pick-up, 6 configurable on Canbus version)
- DSE2130,DSE2157,DSE2548 expansion module can be connected
- Support 0-10V or 4-20mA oil pressure sensor

Main features:

- Multi language display
- Mains failure self starting
- The running time of the engine can be recorded to facilitate the maintenance and repair of the unit
- User-friendly set-up and button layout
- LCD display can display multiple parameters at the same time
- Support EFI engine
- IP65 rating (with optional gasket)
- PC and front panel configuration
- 100 event records
- Data recording and trend analysis

Protection:

- Two sets of protection parameters can be preset
- Normal alarm, electrical trip and shutdown alarm can be set to effectively monitor the engine speed,oil pressure, water temperature and oil level, as well as the frequency, voltage, current and power of the alternator, for complete engine/alternator protection
- Low Oil Pressure
- High water Temperature
- High voltage and low voltage
- Overspeed
- Emergency stop
- Fail to start

AOSIF Soundproof Canopy Introduction:

Standard Type:

- The arc angle structure makes the appearance beautiful and not easy to bump
- High quality coating powder, chemical surface treatment & 100-120um coating thickness greatly improving the anti-corrosion and anti rust level
- Stainless steel hinge & door lock are beautiful and anti-rust
- 2.0mm cold rolled plate used makes the body more solid
- The bottom forklift and loading port design enables easy loading and unloading
- The drainage outlets are all connected to the outside for easy operation
- The sufficient air in & out design ensure long-term and stable operation of the unit
- Isolation net is designed for air inlet, exhaust outlet and muffler outlet to prevent objects from entering the unit
- High density foam used inside effectively reduces noise
- Ceiling Lighting is equipped for easy operation
- The built-in base fuel tank with fuel filler set on the shell facilitates refueling
- Models above medium power range are designed with top hoisting mechanism to facilitate transportation of the unit.

Imitated container type:

- The shell is made of 3.0mm hot rolled steel plate so as to withstand the lifting capacity of 15-ton without deformation
- The switch cabinet and control panel are respectively set on both sides of the shell for easy maintenance & operation
- The shell looks similar to standard container, and can be loaded into 40HQ container for transportation, which is convenient for shipping
- The lifting eye holes are designed on the top same as the standard container for easy handling
- High density foam used inside effectively reduces noise
- The built-in base fuel tank with fuel filler set on the shell facilitates refueling
- Double emergency stop button set on different surfaces enables quick response to operation requirements
- The shell base is independent from the unit with 3mm thick checkered steel plate floor, which is beautiful & antiskid, and is convenient for overhaul & maintenance of the unit
- The door handle, lock and hinge are all made of stainless steel to avoid rusting
- The air out louver made of the mesh plate with powder coating and pasted with high-density glass fiber is beautiful and not easy to rust, and can further reduce the noise
- Isolation net is designed for air inlet, exhaust outlet and muffler outlet to prevent objects from entering the unit
- The sufficient air in & out design ensure long-term and stable operation of the unit
- The drainage outlets are all connected to the outside for easy operation
- Ceiling Lighting is equipped for easy operation

Standard container type:


- Can be shipped on board directly during transportation
- The mesh plate with powder coating and inner pasted with high-density glass fiber is installed inside the shell, which is beautiful and anti-rust, and can further reduce the noise
- 3mm thick checkered steel plate floor is beautiful & antiskid, and is convenient for overhaul & maintenance of the unit
- Double emergency stop button set on different surfaces enables quick response to operation requirements
- The independent daily fuel tank can be designed to put inside to meet requirements of continuous operation
- The fuel filler is set on the shell to facilitate refueling
- The switch cabinet and control panel are respectively set on both sides of the shell for easy maintenance & operation
- The air in & out louver made of the mesh plate with powder coating and pasted with high-density glass fiber is beautiful and not easy to rust, and can further reduce the noise
- Isolation net is designed for air inlet, exhaust outlet and muffler outlet to prevent objects from entering the unit
- The sufficient air in & out design ensure long-term and stable operation of the unit
- The drainage outlets are all connected to the outside for easy operation
- Ceiling Lighting is equipped for easy operation



Decomposition diagram introduction of AOSIF Typical Canopy



Standard supply scope:



Optional supply scope:

Genset	Engine	Alternator	Control system
<ul style="list-style-type: none"> Tool box Base fuel tank External daily fuel tank Trailer 	<ul style="list-style-type: none"> Fuel heater Fuel and water separator 	<ul style="list-style-type: none"> Temp. detector for winding and bearing PMG Antirust, mildew and salt fog treatment Anti condensation heater 	<ul style="list-style-type: none"> ATS Synchronization System Adjustable earth relay
Breaker	Fuel system	Lub-oil system	Cooling system
<ul style="list-style-type: none"> ABB Schneider 	<ul style="list-style-type: none"> Low fuel level alarm Auto Fuel Pump T Valve 	<ul style="list-style-type: none"> Lub oil heater Temp.-sensor Oil drain Pump 	<ul style="list-style-type: none"> Elec.coolant Heater

Our Promises

- AOSIF Engineering provides a full line of brand new and high quality products.
- Each unit passes strictly loading test in factory before shipment.
- Quality Warranty is provided strictly in accordance with warranty terms.
- Three level service guarantee: Aosif dealers, Service outlets of engine/alternator manufacturers, Aosif service team.



XIAMEN AOSIF ENGINEERING LTD.

Marketing Center: Unit 1001, No.1 of Cheng Yi North Street, Software Park Phase III, Xiamen, China;

Factory: No.1088 Tangbian, Changtai Economic Development Zone, Zhangzhou, Fujian, China.

Website: www.aosif.com



You may get more information from our official account.

Specifications are subject to change without notice.